



## MnDOT ADA Compliance Checklist (Curb Ramp)

SP:  City:  District:   
 Intersection:  Quadrant:   
 Ramp Type:  Const. Year:

Attach a photo of the completed quadrant on the form template from ADA site.

(1) Minimum 4' wide pedestrian access route (PAR) maintained?  Yes  No

(2) Landing slopes (%):  (TH)  (TH)  (SS)  (SS) **TH = Trunk Highway**  
**SS = Side Street**

(3) Are landing dimensions a minimum 4' X 4'?  Yes  No

(4) Are landing(s) located at the top of each ramp and at change(s) in direction and at inverse grades?  Yes  No

(5) Ramp's **running slope (%)**:  TH Initial  TH Secondary  SS Initial  SS Secondary

(6) Ramp's **cross slope (%)**:  TH Initial  TH Secondary  SS Initial  SS Secondary

(7) Gutter **flow line slope (%)**:  TH  SS

(8) Gutter **inslope (%)**:  TH  SS

(9) Roadway **cross slope (%)**:  TH  SS

(10) Do ramps comply with Spec 2521.3?  Yes  No

(11) Do truncated domes cover the entire curb opening and are they properly oriented?  Yes  No

(12) Are gutter line and ramps draining properly and not holding water (check after rain event)  Yes  No

(13) Are there any vertical discontinuities greater than 1/4"?  Yes  No

(14) Are ramps **fully compliant**?

If **NO**, check the reason(s) below. Explain why the ramp didn't meet compliance and how

the ramp has been improved from the pre-construction condition (see ADA Compliance Checklist Guidance for more info and attach pages if needed).

- Topography  Structure(s)  Utilities  Contractor

(15) Was the curb ramp able to be built according to the plan details?  Yes  No

Printed Name:  Date (mm/dd/yyyy):

I certify that the information entered on this form is accurate to the best of my knowledge and that I fully understand the checklist standards and am qualified to carry out the inspection.