

## Determining the Angle and Axis of Rotation of a Resilient Modulus Specimen

Bruce Tanquist

1/28/2005

The angle of rotation is defined as the angle between the normal vector of the plane defined by the 3 LVDT deflections and a vertical vector.

Plane equation:

$$Ax + By + Cz + D = 0 \quad (1)$$

Angle between the normals of two planes<sup>1</sup>

$$\cos \tau = \frac{A_1 A_2 + B_1 B_2 + C_1 C_2}{\sqrt{A_1^2 + B_1^2 + C_1^2} \sqrt{A_2^2 + B_2^2 + C_2^2}} \quad (2)$$

Plane passing through Three Points  $\mathbf{P}_i$ ,  $\mathbf{P}_j$ ,  $\mathbf{P}_k$  (Tuma, p. 50)

$$\begin{vmatrix} y_i & z_i & 1 \\ y_j & z_j & 1 \\ y_k & z_k & 1 \end{vmatrix} x + \begin{vmatrix} z_i & x_i & 1 \\ z_j & x_j & 1 \\ z_k & x_k & 1 \end{vmatrix} y + \begin{vmatrix} x_i & y_i & 1 \\ x_j & y_j & 1 \\ x_k & y_k & 1 \end{vmatrix} z = \begin{vmatrix} x_i & y_i & z_i \\ x_j & y_j & z_j \\ x_k & y_k & z_k \end{vmatrix} \quad (3)$$

Horizontal Plane Equation:  $z = 0$

### LVDT readings

Three points, 120° apart when projected in the X,Y plane:

$$\mathbf{P}_1 = (R, 0, \delta_1) \quad (4)$$

$$\mathbf{P}_2 = \left( -\frac{R}{2}, \frac{R\sqrt{3}}{2}, \delta_2 \right) \quad (5)$$

$$\mathbf{P}_3 = \left( -\frac{R}{2}, -\frac{R\sqrt{3}}{2}, \delta_3 \right) \quad (6)$$

Where

$R$  = radius of specimen

$\delta_i$  = peak deflection of LVDT<sub>*i*</sub>

---

<sup>1</sup> Tuma, Jan J., Engineering Mathematics Handbook, 3<sup>rd</sup> Ed., McGraw-Hill, Inc., 1987, p. 51.

### Equation for LVDT Plane

Solving determinants in Equation 3 using coordinates from Equations 4, 5, and 6:

$$A = \sqrt{3}R \left( \frac{\delta_2}{2} + \frac{\delta_3}{2} - \delta_1 \right) \quad (7)$$

$$B = \frac{3}{2}R(\delta_3 - \delta_2) \quad (8)$$

$$C = \frac{3\sqrt{3}}{2}R^2 \quad (9)$$

$$D = -\frac{\sqrt{3}}{2}R^2(\delta_1 + \delta_2 + \delta_3) \quad (10)$$

### Angle of Rotation, $\theta$ (Angle between normal of LVDT plane and vertical)

Substituting Equations 7, 8, 9, and 10 into Equation 2:

$$\cos \theta = \frac{\frac{3}{2}R}{\sqrt{\delta_1^2 + \delta_2^2 + \delta_3^2 - \delta_1\delta_2 - \delta_1\delta_3 - \delta_2\delta_3 + \frac{9}{4}R^2}} \quad (11)$$

In terms of diameter,  $D$ :

$$\cos \theta = \frac{\frac{3}{4}D}{\sqrt{\delta_1^2 + \delta_2^2 + \delta_3^2 - \delta_1\delta_2 - \delta_1\delta_3 - \delta_2\delta_3 + \frac{9}{16}D^2}} \quad (12)$$

### Axis of Rotation

The axis of rotation is the intersection of the LVDT plane with the horizontal plane:

$$z = \frac{\delta_1 + \delta_2 + \delta_3}{3} \quad (13)$$

The equation for the intersection of two planes in the X,Y plane is (Tuma, p. 51):

$$\begin{vmatrix} C_1 & C_2 \\ A_1 & A_2 \end{vmatrix} x + \begin{vmatrix} C_1 & C_2 \\ B_1 & B_2 \end{vmatrix} y + \begin{vmatrix} C_1 & C_2 \\ D_1 & D_2 \end{vmatrix} = 0 \quad (14)$$

Substituting Equations 7, 8, 9, 10, and 13 into Equation 14 results in the equation for the axis of rotation:

$$\sqrt{3}R \left( \frac{\delta_2}{2} + \frac{\delta_3}{2} - \delta_1 \right) x + \frac{3}{2}R(\delta_3 - \delta_2)y = 0 \quad (15)$$