



TABLE						
PAD TYPE	LOCATION	BEAM SIZE	BEARING PAD SIZE			SHAPE FACTOR
			A	B	D ①	
		--RB, --M, MN--	12	24	1/2	8.0
		--MH	12	30	1/2	8.6

**NOTES:**

USE NEOPRENE OR NATURAL RUBBER AND FABRICATE PAD IN ACCORDANCE WITH SPEC. 3741.

PAYMENT FOR ELASTOMERIC BEARING PAD INCLUDED IN ITEM "ELASTOMERIC BEARING PAD" PER EACH.

① "D" INDICATES THE THICKNESS OF THE BEARING PAD.

*DESIGNER NOTE*  
 (REMOVE DESIGNER NOTE PRIOR TO PLOTTING FINAL PLAN);  
 INSERT TABLE VALUES AS NEEDED AND DELETE UNUSED DATA.  
 USE 1/2" UNREINFORCED PAD WITH CONTINUITY DIAPHRAGMS OR INTEGRAL ABUTMENTS.

APPROVED: OCTOBER 22, 2019

*Kevin Westrom*  
STATE BRIDGE ENGINEER

STATE OF MINNESOTA  
DEPARTMENT OF TRANSPORTATION

ELASTOMERIC BEARING PAD  
(PRESTRESSED CONCRETE BEAMS)

REVISION

DETAIL NO.

B305