

Figure 5-397.302
Stabilized Aggregate Slope Paving Under Bridges

Approved, and signed, September 26, 2003. Last date revised: September 11, 2014

Revised 09-11-2014

At SECTION A-A:

- Changed note pointing to the geotextile *From*: Place geotextile, Spec. 3733, under aggregate in areas under bridge deck drain to reduce erosion from splashing. *To*: Place geotextile, Spec. 3733 Type 3, under aggregate in areas under bridge deck drain to reduce erosion from splashing.

Revised 02-27-2013

At LAYOUT FOR SLOPES AT HIGH ABUTMENTS:

- Removed the Δ 2'-0" dimension from the side of the abutment and added it to both sides of the slope paving with "Outside Face of Bridge Coping" note.

At SECTION A-A:

- Added note with leader line "Bituminous Surface Coating per Spec. 2514."
- Added an additional 2" x 6" treated timber plank to the view to show them side by side (doubled).
- Changed the note pointing to the timber planks to read "Double Nominal 2" x 6" Treated Timber Plank Spec. 3426 (1500P.S.I.) ①

At SECTION B-B:

- Added an additional 2" x 6" treated timber plank to the view to show them side by side (doubled).
- Changed the note pointing to the timber planks to read "Double Nominal 2" x 6" Treated Timber Plank Spec. 3426 (1500P.S.I.) ①

At SECTION C-C:

- Added an additional 2" x 6" treated timber plank to the view to show them side by side (doubled).
- Changed the note pointing to the timber planks to read "Double Nominal 2" x 6" Treated Timber Plank Spec. 3426 (1500P.S.I.) ①

Changed GENERAL NOTE to read "GENERAL NOTES"

Under GENERAL NOTES:

- Added note "Refer to Specification 2514 for additional information."
- Added numbered note ① "Preservative Treatment per Spec. 3491, Table 3491-1, product and usage Category E2, AWP A Use Category UC4B. Refer to MNDOT Approved Products List."

Approved, and signed, September 26, 2003