

**Figure 5-397.632(B)**

**Waterproof Expansion Device (Raised Median or Integral Sidewalk with S Barrier and Curb)**

Approved, and signed, August 24, 2016. Last date revised: October 22, 2019.

**Revised: 10-22-2019**

At the INSIDE ELEVATION of CONCRETE CURB and at OUTSIDE ELEVATION of S BARRIER and at MEDIAN ELEVATION:

- Added numbered note ① to the details.

Throughout the Standard:

- Added (Typ.) to the See Bent Stud Detail 1'-6" Max. Spg. note.

**Revised: 02-22-2018**

Throughout the Standard:

- Changed the flathead cap screw length from a 1" flathead cap screw to a 1 1/2" flathead cap screw.
- Changed the terminology when referring to recessing the cover plates, changed the term "below" to "from" at all locations.

At OUTSIDE ELEVATION of S BARRIER:

- Changed the look of the slotted hole in the cover plate to reflect the actual size.
- At the slotted hole note, removed the word "DIA." from the dimensions of the long slotted hole.

At INSIDE ELEVATION of CONCRETE CURB:

- At the slotted hole note, removed the word "DIA" from the dimensions of the long slotted hole.

At SECTION THROUGH BARRIER AND CURB – INTEGRAL SIDEWALK:

- Added note: \*Top of Block Out.
- Added an asterisk to the Block Out dimensions.

At MEDIAN ELEVATION:

- Changed the note for the coupling nut and bolt from a 4" to a 3" bolt length.

Under Notes:

- Removed the reference to "Standard Figure 5-397.627(B)" and replaced with "other waterproof expansion device sheet" in two locations.

Added bubbled Designer Note: "Always include Standard Figure 5-397.627(B) along with this sheet".

**Approved, and signed, August 24, 2016**

NEW STANDARD