

**STATE OF MINNESOTA**  
**Crane RISE CRANE Cab & Chassis**

Price quote for:

Contract End Date March 2018

|                  |  |
|------------------|--|
| Vendor Name:     | <b>Bert's Truck Equipment, Inc</b>                               |
| Contact Person:  | <b>Jim McLaughlin</b>  |
| Street Address:  | <b>3804 Hwy 75 North</b>   |
| P.O. Box:        | <b>PO 336</b>  |
| City, State, Zip | <b>Moorhead, MN 56560</b>  |
| Phone #:         | <b>218-233-8681</b>  |
| Toll Free #:     | <b>800-232-3787</b>  |
| Fax #:           | <b>218-233-9548</b>  |
| Email Address:   | <a href="mailto:jimmc@bertsonline.com">jimmc@bertsonline.com</a> |
|                  | <b>www.bertsonline.com or www.liftmoore.com</b>                  |

| Spec #     | Information Requested   | Answer   |
|------------|---|--|
| <b>1.0</b> | <b>MAKE AND MODEL</b>   | Lemco 8000 Log Loader                                      |
|            | Required Frame RBM, SM & PSI of steel   | N/A  |
|            | Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity                  | Capacity at 10' = 8500 lbs, 15' = 5900 lbs, 20' = 4000 lbs |
|            | Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length |  |
|            | Main Boom   | N/A  |
|            | First Extension   | N/A  |
|            | Second Extension  | N/A  |
|            | Third Extension   | N/A  |
|            | Fourth Extension  | N/A  |
|            | Fifth Extension   | N/A  |
|            | Sixth Extension   | N/A  |
|            | Seventh Extension   | N/A  |
|            | Crane weight  | 7600 LB  |
|            | Total vertical reach  | 32' @ 7' Radius (may vary depending on Options)            |
|            | Horizontal hook approach from centerline of rotation  | N/A  |
|            | Vertical hook approach from mounting surface  | N/A  |
|            | Total horizontal reach  | 26'6"  |
|            | Below chassis frame reach   | All the way to the ground                                  |
|            | Boom stowed height from mounting surface  | Varies with chassis and options                            |
|            | Crane mounting space requirement  | 36"  |

# STATE OF MINNESOTA

[www.bertsonline.com](http://www.bertsonline.com) or [www.liftmoore.com](http://www.liftmoore.com)

| Spec # | Information Requested  | Answer   |
|--------|--|--|
|        | Distance from back of cab to crane clearance                           | 3"   |
|        | Distance from crane to front of body clearance                         | 3"   |
|        | Crane rotation & rotation working area                                 | Continous Rotation   |
|        | Rotation system brake  | N/A  |
|        | Rotation system Drive  | Hydraulic Gear Drive   |
|        | Rotational torque in ft-lb's   | N/A  |
|        | Outrigger description, width & design                                  | A-frame  |
|        | Outrigger hydraulic description (independent down, stroke length, etc. | Independent Down, 3.5" Bore, 43" strock, 2" solid Chrome Steel Rod   |
|        | Outrigger pad size & type  | 16"x16" with curled edges  |
|        | Throttle control, if any   | N/A  |
|        | Hydraulic pump type, GPM, PSI  | 60 GPM, 2400 PSI   |
|        | Hydraulic oil reservoir size/description                               | 40 gallon, intank filter with sight gauge  |
|        | Is Hydraulic reservoir heated  | No   |
|        | Hydraulic fluid type   | Ricon MV, All season   |
|        | Control locations & Description  | Full support seat position for maximum operator comfort, two joystick control operating system, convenient full reach control              |
|        | Control valve type   | Stacked valves   |
|        | Wireless remote included   | Optional   |
|        | Number of wireless remote functions                                    | Optional   |
|        | Boom Cylinder description  | Main boom Cylinder = 6" bore, 36" stroke, 3" Solid Chrome steel rods. Stick Boom cylinder = 6" bore, 30" stroke, 3" solid chrome steel rod |
|        | Crane rating   | None   |
|        | Country of origin for crane  | USA, Hill City, MN   |
|        | Crane Overall Weight   | # 7600 +/-   |
|        | Crane Stowed Center of Gravity   | Varies depending on chassis  |
|        | Warranty   | Linited One year   |

**BASE UNIT PRICE:** \$ 61,695.00  
 Includes Installtion (FOB Hill City, MN)

STATE OF MINNESOTA  
**PRICING PAGE**  
**Crane Installed on Cab & Chassis**

VENDOR: Bert's Truck Equipment, Inc  
 MAKE/MOD Lemco 8000

| Spec # | Description   | Qty | Price        | Subtotal |
|--------|---|-----|--------------|----------|
| 1.0    | <b>BASE UNIT PRICE:</b>   |     | \$ 61,695.00 | \$ -     |
| 2.0    | <b>CRANE EXTENSION OPTIONS</b>  |     |              |          |
| 2.1    |   |     | N/A          |          |
| 3.0    | <b>OUTRIGGER OPTIONS</b>  |     |              |          |
| 3.1    | Hydraulic Down and Out ILO Standard A-Frame Add   |     | N/A          |          |
| 4.0    | <b>REMOTE CONTROLS</b>  |     |              |          |
| 4.1    | Multi-Function Wireless Remote control add  |     | \$ 13,495.00 | \$ -     |
| 5.0    | <b>ATTACHMENTS</b>  |     |              |          |
| 5.1    | 48" brush Grapple ILO Standard Grapples add   |     | \$ 2,995.00  | \$ -     |
| 6.0    | <b>OTHER OPTIONS</b>  |     |              |          |
| 6.1    | Out of Stow alarm   |     | N/A          |          |
| 6.2    | 22' Custom BTE HD Log Box, Up to 72", 3/16" Grade 50 sides, 1/4" AR400 Floor, painted one standard Color, and installed       |     | \$ 20,975.00 | \$ -     |
| 6.3    | Power beyond sleeve with single valve for body hoist  |     | \$ 775.00    | \$ -     |
| 6.4    | Extra Valve for Power beyond Sleeve   |     | \$ 775.00    | \$ -     |
| 6.5    | Standard Air shift PTO for Manual transmission  |     | \$ 695.00    | \$ -     |
| 6.6    | Hot Shift PTO   |     | \$ 2,195.00  | \$ -     |
| 6.7    | Extended Shaft Hot shift PTO  |     | \$ 2,795.00  | \$ -     |
| 6.8    | DP 20AJ, 20,000 LB Hydraulic Winch, 80' 5/8" HD Wire Rope, 22K Hook, Installed (Contact distributor for chassis requirements) |     | \$ 9,195.00  | \$ -     |
| 6.9    | Knapheide KH-2527L Hoist less hydraulics, Installed   |     | \$ 5,995.00  | \$ -     |
| 7.0    | <b>CUSTOM WORK</b>  |     |              |          |
| 7.1    | Shop labor for chassis modifications (Per hour)   |     | \$ 110.00    | \$ -     |
| 8.0    | <b>DISCOUNT OFF LIST PRICE FOR RELATED PARTS AND ACCESSORIES</b>  |     | 0 % Discount |          |
|        | Price List Date and Number  |     |              |          |
| 9.0    | <b>DELIVERY CHARGES</b>   |     |              |          |
|        | DELIVERY STARTING POINT - City, State, Zip  |     |              |          |
|        | Hill City, MN or Moorhead MN  |     |              |          |
|        | Price per loaded mile   |     | \$ 2.50      | \$ -     |
| 10.0   | <b>PER HOUR (HOURLY SHOP RATE)</b>  |     |              |          |
| 10.1   | <b>HOURLY RATE FOR EQUIPMENT INSPECTION AND REPAIR</b>  |     | \$ 110.00    | \$ -     |
| 10.2   | <b>HOURLY RATE FOR INITIAL INSPECTION/DIAGNOSTIC</b>  |     | \$ 110.00    | \$ -     |
| 10.3   | <b>HOURLY RATE FOR MECHANICAL REPAIRS</b>   |     | \$ 110.00    | \$ -     |
|        | <b>Total Cost:</b>  |     |              |          |