

## Discount Off List

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

### PRICING METHOD 2 - PERCENTAGE DISCOUNT OFF LIST

1.0	<b>CRANE/MAKE</b>	<b>Venco Venturo</b>
	Warranty	<b>1 year from installation</b>
	Percentage Discount to be applied to Price List	<b>0% Discount</b>
	Date & Price List I.D. Number	<b>N/A</b>
2.0	<b>OPTIONS (If not included in list) NA</b>	
3.0	<b>EXTENDED WARRANTY OPTIONS NA</b>	
4.0	<b>DELIVERY CHARGES</b>	
	<b>DELIVERY STARTING POINT - City, State, Zip</b>	
	<b>Lake Crystal, MN 56055 or Fridley, MN 55432</b>	
	<b>Price per loaded mile</b>	<b>\$1.95</b>
5.0	<b>DISCOUNT OFF LIST PRICE FOR RELATED PARTS AND ACCESSORIES</b>	
	% Discount	<b>N/A</b>
	Price List Date and Number	<b>N/A</b>
6.0	<b>HOURLY SHOP RATE (Per Hour)</b>	
6.1	<b>EQUIPMENT INSPECTION AND REPAIR</b>	<b>\$ 95.00</b>
6.2	<b>HOURLY RATE FOR INITIAL INSPECTION/DIAGNOSTIC</b>	<b>\$ 95.00</b>
6.3	<b>HOURLY RATE FOR MECHANICAL REPAIRS</b>	<b>\$ 95.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo HT25KX
	Required Frame RBM, SM & PSI of steel	Recommended 11,000 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	5,000 lbs. @ 5 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Proportional Hydraulic 5 ft.,
	First Extension	Proportional Hydraulic 10
	Second Extension	Proportional Hydraulic 16
	Third Extension	Proportional Hydraulic 20
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	1,535 lbs.

Total vertical reach	21-1/2' @ 75 degrees
Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	20'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	30-5/8"
Crane mounting space requirement	16" x 16" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	400 degrees power
Rotation system brake	Capacity Overload Shut-
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed- manual out and hydraulic down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	Optional only w/
Hydraulic pump type, GPM, PSI	Pump Type: A Flange, 5/8" – 9 Spline GPM: 4.0 @ 1000 RPM
Hydraulic oil reservoir size/description	10 GAL. Bulkhead Mount Reservoirs include 100 mesh suction scree, 10 micron return filter, return and supply pressure
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A

Control locations & Description	Wireless Remote, pistol-grip controller w/ LCD Display Screen Text and Transmitter handle vibrations
Control valve type	Proportional
Wireless remote included	Yes
Number of wireless remote functions	(All functions are on
Boom Cylinder description	Load-Holding
Crane rating	25,000 FT-LBS crane
Country of origin for crane	USA
Crane Overall Weight	1,535 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.
<b>BASE UNIT PRICE:</b>	<b>\$21,090.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo HT30KX
	Required Frame RBM, SM & PSI of steel	Recommended 11,000 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	5,000 lbs. @ 6 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Proportional Hydraulic 6 ft.,
	First Extension	Proportional Hydraulic 10
	Second Extension	Proportional Hydraulic 16
	Third Extension	Proportional Hydraulic 20
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A

Crane weight	1,535 lbs.
Total vertical reach	21-1/2' @ 75 degrees
Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	20'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	30-5/8"
Crane mounting space requirement	16" x 16" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	400 degrees power
Rotation system brake	Capacity Overload Shut-
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed- manual out and hydraulic
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	Optional only w/
Hydraulic pump type, GPM, PSI	Pump Type: A Flange, 5/8" – 9 Spline GPM: 4.0 @ 1000 RPM
Hydraulic oil reservoir size/description	10 GAL. Bulkhead Mount Reservoirs include 100 mesh suction scree, 10 micron return filter, return and supply pressure
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A

Control locations & Description	Wireless Remote, pistol-grip controller w/ LCD
Control valve type	Proportional
Wireless remote included	Yes
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	Load-Holding
Crane rating	30,000 FT-LBS crane
Country of origin for crane	USA
Crane Overall Weight	1,535 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in
<b>BASE UNIT PRICE:</b>	<b>\$21,750.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo HT45KX
	Required Frame RBM, SM & PSI of steel	Recommended 16,000 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	7,800 lbs. @ 6 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Proportional Hydraulic 6 ft.,
	First Extension	Proportional Hydraulic 10
	Second Extension	Proportional Hydraulic 16
	Third Extension	Proportional Hydraulic 20
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	1,900 lbs.

Total vertical reach	21-1/2' @ 75 degrees
Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	20'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	36-7/8"
Crane mounting space requirement	16" x 16" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	400 degrees power
Rotation system brake	Capacity Overload Shut-
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed-
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	Optional only w/
Hydraulic pump type, GPM, PSI	Pump Type: B Flange, 7/8" – 13 Spline           GPM: 12 @ 1200 RPM
Hydraulic oil reservoir size/description	25 GAL. Bulkhead Mount Reservoirs include 100 mesh suction screen, 10 micron return filter, return and supply pressure
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A

Control locations & Description	Wireless Remote, pistol-grip controller w/ LCD Display Screen Text and Transmitter handle vibrations
Control valve type	Proportional
Wireless remote included	Yes
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	45,600 FT-LBS crane
Country of origin for crane	USA
Crane Overall Weight	1,900 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.
<b>BASE UNIT PRICE:</b>	<b>\$23,930.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo HT40KX-25
	Required Frame RBM, SM & PSI of steel	Recommended 16,000 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	7,800 lbs. @ 6 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Proportional Hydraulic 6 ft.,
	First Extension	Proportional Hydraulic 12
	Second Extension	Proportional Hydraulic 18
	Third Extension	Proportional Hydraulic 25 ft., 1,500 lbs.
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	1,975 lbs.

Total vertical reach	26' @ 75 degrees
Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	25'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	36-7/8"
Crane mounting space requirement	16" x 16" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	400 degree power
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed- hydraulic out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	Optional only w/ Proportional Controls
Hydraulic pump type, GPM, PSI	Pump Type: B Flange, 7/8" – 13 Spline GPM: 12 @ 1200 RPM (if needed)
Hydraulic oil reservoir size/description	25 GAL. Bulkhead Mount Reservoirs include 100 mesh suction scree, 10 micron return filter, return and supply pressure gauges, sight glass and breather cap. (if needed)
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A

Control locations & Description	Wireless Remote, pistol-grip controller w/ LCD Display Screen Text and Transmitter handle vibrations
Control valve type	Proportional
Wireless remote included	Yes
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	45,600 FT-LBS crane moment rating
Country of origin for crane	USA
Crane Overall Weight	1,975 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in
<b>BASE UNIT PRICE:</b>	<b>\$25,000.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo HT55KX
	Required Frame RBM, SM & PSI of steel	Recommended 20,500 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	8,500 lbs. @ 6 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Proportional Hydraulic 6 ft., 8,500 lbs.
	First Extension	Proportional Hydraulic 10
	Second Extension	Proportional Hydraulic 16
	Third Extension	Proportional Hydraulic 20
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	1,975 lbs.
	Total vertical reach	21' @ 75 degrees
	Horizontal hook approach from centerline of rotation	N/A

Vertical hook approach from mounting surface	N/A
Total horizontal reach	20'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	36-7/8"
Crane mounting space requirement	16" x 16" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	400 degree power
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed- hydraulic out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	Optional only with Proportional Controls
Hydraulic pump type, GPM, PSI	Pump Type: B Flange, 7/8" – 13 Spline      GPM: 12 @ 1200 RPM (if needed)
Hydraulic oil reservoir size/description	10 or 25 GAL. Bulkhead Mount      Reservoirs include 100 mesh suction scree, 10 micron return filter, return and supply pressure gauges, sight glass and breather cap. (if needed)
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Wireless Remote, pistol- grip controller w/ LCD Display Screen Text and Transmitter handle vibrations

Control valve type	Proportional
Wireless remote included	Yes
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	55,000 FT-LBS crane moment rating
Country of origin for crane	USA
Crane Overall Weight	1,975 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$25,560.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo HT55KX-25
	Required Frame RBM, SM & PSI of steel	Recommended 20,500 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	8,500 lbs. @ 6 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Proportional Hydraulic 6', 8,500 lbs.
	First Extension	Proportional Hydraulic 12',
	Second Extension	Proportional Hydraulic 18',
	Third Extension	Proportional Hydraulic 25
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	2,125 lbs.
	Total vertical reach	26 ft. @ 75 degrees

Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	25 ft.
Below chassis frame reach	N/A
Boom stowed height from mounting surface	36-7/8"
Crane mounting space requirement	16" x 16" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	400 degrees power
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed-
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	Optional only with Proportional Controls
Hydraulic pump type, GPM, PSI	GPM: 12 @ 1200 RPM Pump Type: B Flange, 7/8" – 13 Spline (if
Hydraulic oil reservoir size/description	10 or 25 GAL. Bulkhead Mount Reservoirs include 100 mesh suction scree, 10 micron return filter, return and supply pressure gauges, sight glass and breather cap. (if needed)
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Wireless Remote, pistol-grip controller w/ LCD Display Screen Text and Transmitter handle vibrations
Control valve type	Proportional

Wireless remote included	Yes
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	55,000 FT-LBS crane moment rating
Country of origin for crane	USA
Crane Overall Weight	2,125 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Ventura to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$26,560.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo HT66KX-25
	Required Frame RBM, SM & PSI of steel	Recommended 33,000 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	11,500 lbs. @ 6 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Proportional Hydraulic 6 ft.,
	First Extension	Proportional Hydraulic 12
	Second Extension	Proportional Hydraulic 18
	Third Extension	Proportional Hydraulic 25 ft., 2,450 lbs.
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	2,600 lbs.
	Total vertical reach	26' @ 75 degrees
	Horizontal hook approach from centerline of rotation	N/A

Vertical hook approach from mounting surface	N/A
Total horizontal reach	25'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	35-1/2"
Crane mounting space requirement	17-1/2" x 17-1/2" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	400 degrees power
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Front & Rear Outriggers needed Rear Outriggers: Hydraulic out & down      Front Outriggers: Manual out & Hydraulic down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	Optional, Includes pendant switches, wiring harness and relays to supply a 12V or ground signal to the
Hydraulic pump type, GPM, PSI	GPM: 12 @ 1200 RPM Pump Type: B Flange, 7/8" – 13 Spline (if needed)
Hydraulic oil reservoir size/description	40 GAL. Bulkhead Mount Reservoirs include 100 mesh suction scree, 10 micron return filter, return and supply pressure gauges, sight glass and breather cap. (if needed)
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A

Control locations & Description	Wireless Remote, pistol-grip controller w/ LCD Display Screen Text and Transmitter handle vibrations
Control valve type	N/A
Wireless remote included	Yes
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	66,000 FT-LBS crane moment rating
Country of origin for crane	USA
Crane Overall Weight	2,600 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$29,040.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo DT7K
	Required Frame RBM, SM & PSI of steel	Recommended 8,000 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	1,200 lbs. @ 6 ft. 1,050 lbs. @ 7 ft. 900 lbs. @ 8 ft. 800 lbs. @ 9 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Manual 6', 1,200 lbs.
	First Extension	Manual 7', 1,050 lbs.
	Second Extension	Manual 8' 900 lbs.
	Third Extension	Manual 9' 800 lbs.
	Fourth Extension	Manual 10' 700 lbs.
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	310 lbs.
	Total vertical reach	10' @ 60 degrees

Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	10'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	31"
Crane mounting space requirement	12" x 12" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Continuous Manual Rotation
Rotation system brake	8-position base lock to hold mast firmly in position while in use and while traveling
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Outriggers needed, manual out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 15 Ft Cord with Quick Disconnect
Control valve type	N/A
Wireless remote included	No
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A

Crane rating	7,000 FT-LBS crane moment rating
Country of origin for crane	USA
Crane Overall Weight	310 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.
<b>BASE UNIT PRICE:</b>	<b>\$5,830.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ET6K
	Required Frame RBM, SM & PSI of steel	Recommended 8,000 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	1,000 lbs. @ 6 ft. 845 lbs. @ 7 ft. 740 lbs. @ 8 ft. 652 lbs. @ 9 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Manual 6', 1,000 lbs.
	First Extension	Manual 7', 845 lbs.
	Second Extension	Manual 8', 740 lbs.
	Third Extension	Manual 9', 652 lbs.
	Fourth Extension	Manual 10', 576 lbs.
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	380 lbs.
	Total vertical reach	11' @ 75 degrees

Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	10'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	24-1/4"
Crane mounting space requirement	10-1/2" x 10-1/2" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	360 degree Continuous Power Rotation
Rotation system brake	Dual-Load Applied and Dynamic Braking System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Outriggers needed, manual out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 20 ft. Cord and Quick Disconnect
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	Load-Holding Counterbalance Valves on All Cylinders

Crane rating	6,000 FT-LBS crane moment rating
Country of origin for crane	USA
Crane Overall Weight	380 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$9,340.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ET8K
	Required Frame RBM, SM & PSI of steel	Recommended 8,000 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	1,350 lbs. @ 6 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Manual 6', 1,350 lbs.
	First Extension	Manual 10', 825 lbs.
	Second Extension	Manual 14', 600 lbs.
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	560 lbs.
	Total vertical reach	14.5' @ 75 degrees
	Horizontal hook approach from centerline of rotation	N/A

Vertical hook approach from mounting surface	N/A
Total horizontal reach	14'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	26-1/4"
Crane mounting space requirement	14" x 14" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Continuous Power Rotation & Elevation
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outrigger needed, manual out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 25 FT Cord and Quick Disconnect
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	8,000 FT-LBS crane moment rating
Country of origin for crane	USA
Crane Overall Weight	560 lbs.

Crane Stowed Center of Gravity

N/A

Warranty

Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.

**BASE UNIT PRICE:**

\$10,590.00

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ET8K(X)
	Required Frame RBM, SM & PSI of steel	Recommended 8,000 lb.
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	1,325 lbs. @ 6 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	1st stage: Hydraulic 6', 1,350 lbs.
	First Extension	2nd stage: Hydraulic 10', 825 lbs.
	Second Extension	3rd stage: Manual 14', 600 lbs.
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	650 lbs.
	Total vertical reach	14.5' @ 75 degrees

Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	14'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	26-1/4"
Crane mounting space requirement	14" x 14" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Continuous Power Rotation & Elevation
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outrigger needed, manual out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 25 FT Cord and Quick Disconnect
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	8,000 FT-LBS crane moment rating

Country of origin for crane USA

Crane Overall Weight 650 lbs.

Crane Stowed Center of Gravity N/A

Warranty Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.

**BASE UNIT PRICE:** \$11,720.00

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ET12KX-15
	Required Frame RBM, SM & PSI of steel	Recommended 8,800 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	1,800 lbs. @ 7 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Hydraulic 7', 1,800 lbs.
	First Extension	Hydraulic 11', 1,100 lbs.
	Second Extension	Manual 15', 800 lbs.
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	700 lbs.
	Total vertical reach	15.5' @ 75 degrees
	Horizontal hook approach from centerline of rotation	N/A

Vertical hook approach from mounting surface	N/A
Total horizontal reach	15'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	26-1/4"
Crane mounting space requirement	14" x 14" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Continuous Power Rotation & Elevation
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outrigger needed, manual out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 25 FT Cord and Quick Disconnect
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	12,000 FT-LB Moment Rating
Country of origin for crane	USA
Crane Overall Weight	700 lbs.

Crane Stowed Center of Gravity

N/A

Warranty

Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.

**BASE UNIT PRICE:**

\$12,410.00

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ET12KXP-16
	Required Frame RBM, SM & PSI of steel	Recommended 8,800 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	1,250 lbs. @ 9 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Hydraulic 9', 1,250 lbs.
	First Extension	Hydraulic 16', 750 lbs.
	Second Extension	N/A
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	700 lbs.
	Total vertical reach	16' @ 75 degrees
	Horizontal hook approach from centerline of rotation	N/A

Vertical hook approach from mounting surface	N/A
Total horizontal reach	16'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	26-3/4"
Crane mounting space requirement	14" x 14" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Continuous Power Rotation
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outrigger needed, manual out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 25 FT Cord and Quick Disconnect
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	12,000 FT-LB Moment Rating
Country of origin for crane	USA
Crane Overall Weight	700 lbs.

Crane Stowed Center of Gravity

N/A

Warranty

Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.

**BASE UNIT PRICE:**

\$12,410.00

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ET16K(X)
	Required Frame RBM, SM & PSI of steel	Recommended 10,500 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	2,000 lbs. @ 8 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Hydraulic 8 ft., 2,000 lbs.
	First Extension	Hydraulic 12', 1,250 lbs.
	Second Extension	Manual 16', 900 lbs.
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	1,020 lbs.
	Total vertical reach	17' @ 75 degrees
	Horizontal hook approach from centerline of rotation	N/A

Vertical hook approach from mounting surface	N/A
Total horizontal reach	16'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	26-5/8"
Crane mounting space requirement	14" x 14" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Continuous Power Rotation & Elevation
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed, manual out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 25 FT Cord and Quick Disconnect
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	16,000 FT-LB Moment Rating
Country of origin for crane	USA

Crane Overall Weight 1,020 lbs.

Crane Stowed Center of Gravity N/A

Warranty Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.

**BASE UNIT PRICE:** \$14,480.00

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ET18K(X)
	Required Frame RBM, SM & PSI of steel	Recommended 10,500 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	2,250 lbs. @ 8 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Hydraulic 8', 2,250 lbs.
	First Extension	Hydraulic 12', 1,500 lbs.
	Second Extension	Manual 16', 1,125 lbs.
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	1,020 lbs.
	Total vertical reach	17' @ 75 degrees
	Horizontal hook approach from centerline of rotation	N/A

Vertical hook approach from mounting surface	N/A
Total horizontal reach	16'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	26-5/8"
Crane mounting space requirement	14" x 14" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Continuous Power Rotation & Elevation
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed, manual out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 25 ft. Cord and Quick Disconnect
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	18,000 FT-LB Moment Rating
Country of origin for crane	USA

Crane Overall Weight 1,020 lbs.

Crane Stowed Center of Gravity N/A

Warranty Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.

**BASE UNIT PRICE:** \$14,960.00

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ET25KX
	Required Frame RBM, SM & PSI of steel	Recommended 10,500 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	5,000 lbs. @ 5 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Hydraulic 10', 2,500 lbs.
	First Extension	Hydraulic 16', 1,575 lbs.
	Second Extension	Hydraulic 20', 1,250 lbs.
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	1,500 lbs.
	Total vertical reach	22' @ 75 degrees

Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	20'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	28-7/8"
Crane mounting space requirement	16" x 16" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Continuous Power Rotation
Rotation system brake	Capacity Overload Shut-
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed,
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 25 FT Cord and Quick
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	Load-holding

Crane rating	25,000 FT-LB Moment
Country of origin for crane	USA
Crane Overall Weight	1,500 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$19,070.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ET30KX
	Required Frame RBM, SM & PSI of steel	Recommended 11,000 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	5,000 lbs. @ 6 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	1st stage: Hydraulic 10', 3,000 lbs.
	First Extension	2nd stage: Hydraulic 16', 1,875 lbs.
	Second Extension	3rd stage: Hydraulic 20', 1,500 lbs.
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	1,500 lbs.
	Total vertical reach	21' @ 75 degrees

Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	20'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	28-7/8"
Crane mounting space requirement	16" x 16" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Continuous Power Rotation & Elevation
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed, manual out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 25 FT Cord and Quick Disconnect
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	Load-holding counterbalance on all cylinders

Crane rating	30,000 FT-LB Moment Rating
Country of origin for crane	USA
Crane Overall Weight	1,500 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.
<b>BASE UNIT PRICE:</b>	<b>\$19,680.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ET36KX
	Required Frame RBM, SM & PSI of steel	Recommended 14,500 lb. GVWR Chassis
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	6,000 lbs. @ 6 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Hydraulic 10', 3,600 lbs.
	First Extension	Hydraulic 16', 2,250 lbs.
	Second Extension	Hydraulic 20', 1,800 lbs.
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	1,535 lbs.
	Total vertical reach	21' @ 75 degrees
	Horizontal hook approach from centerline of rotation	N/A

Vertical hook approach from mounting surface	N/A
Total horizontal reach	20'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	28-7/8"
Crane mounting space requirement	16" x 16" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Continuous Power Rotation & Elevation
Rotation system brake	Capacity Overload Shut-Off System
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Rear Outriggers needed, manual out and down
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 25 ft. Cord and Quick Disconnect
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	Load-Holding Counterbalance on All Cylinders
Crane rating	36,000 FT-LBS crane moment rating
Country of origin for crane	USA

Crane Overall Weight 1,535 lbs.

Crane Stowed Center of Gravity N/A

Warranty Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.

**BASE UNIT PRICE:** \$19,990.00

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo CE1500FB
	Required Frame RBM, SM & PSI of steel	N/A
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	800 lbs. @ 5 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Manual 3', 1,500 lbs.
	First Extension	Manual 4', 1,150 lbs.
	Second Extension	Manual 5', 800 lbs.
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	165 lbs.
	Total vertical reach	6.5'

Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	5'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	62"
Crane mounting space requirement	12" x 12" Surface Mounting Socket
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Manual 360-degree
Rotation system brake	Dynamic motor braking for
Rotation system Drive	Band brake provides unlimited controlled load
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Optional adder for jackleg drop down outrigger for
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 12 FT cord with quick
Control valve type	N/A
Wireless remote included	No

Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	4,500 FT-LBS crane
Country of origin for crane	USA
Crane Overall Weight	165 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$3,210.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo CE6K-4
	Required Frame RBM, SM & PSI of steel	N/A
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	1,200 lbs. @ 5 ft. 1,000 lbs. @ 6 ft. 850 lbs. @ 7 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Manual 3', 2,000 lbs.
	First Extension	Manual 4', 1,500 lbs.
	Second Extension	Manual 5', 1,200 lbs.
	Third Extension	Manual 6', 1,000 lbs.
	Fourth Extension	Manual 7', 850 lbs.
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	275 lbs.
	Total vertical reach	11'

Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	7'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	60"
Crane mounting space requirement	10" x 10" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Manual 360-degree
Rotation system brake	Rotation band brake
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Optional Adder for jackleg drop down outrigger for
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 12 FT cord with Quick
Control valve type	N/A
Wireless remote included	No
Number of wireless remote functions	All functions on remote

Boom Cylinder description	N/A
Crane rating	6,000 FT-LB Moment
Country of origin for crane	USA
Crane Overall Weight	275 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$4,010.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo CT2003FB
	Required Frame RBM, SM & PSI of steel	N/A
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	1,000 lbs. @ 5 ft.
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	1st stage: Manual 3', 2,000
	First Extension	2nd stage: Manual 4',
	Second Extension	3rd stage: Manual 5', 1,000
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	235 lbs.
	Total vertical reach	7'

Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	5'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	71-3/4"
Crane mounting space requirement	10" x 10" Mounting Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	360 degree Manual Rotation with 8-position base lock to hold mast firmly in position while in use and while traveling
Rotation system brake	N/A
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Optional Adder for jackleg drop down outrigger for utility body or platform body
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A

Control locations & Description	Remote Control Pendant: 15 FT cord with quick
Control valve type	N/A
Wireless remote included	No
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	6,000 FT-LBS Crane
Country of origin for crane	USA
Crane Overall Weight	235 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$4,080.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo CT310KX
	Required Frame RBM, SM & PSI of steel	Can be installed on trailers, platform, utility, and van
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	1,100 lbs. @ 6-1/2"
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	Hydraulic 4-1/2', 1,750 lbs.
	First Extension	Hydraulic 6-1/2", 1,100 lbs.
	Second Extension	Manual 9-1/4", 755 lbs.
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	490 lbs.

Total vertical reach	13'
Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	9'3"
Below chassis frame reach	4'
Boom stowed height from mounting surface	64-3/4"
Crane mounting space requirement	10-1/2" x 10-1/2" Mounting
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	360 degrees Power
Rotation system brake	Slewing ring fixed – can be placed in tight spaces.
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Manual out and down outriggers available.
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 20 Ft Cord with Quick Disconnect. Audible
Control valve type	N/A
Wireless remote included	No, Optional Adder
Number of wireless remote functions	All functions are on remote

Boom Cylinder description	Load-holding counterbalance valves on
Crane rating	6,650 FT-LB moment
Country of origin for crane	USA
Crane Overall Weight	490 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$11,310.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo VC1000
	Required Frame RBM, SM & PSI of steel	Fits Ford Transit Mid/High Roof & Freightliner/Mercedes
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	N/A
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	1st stage: Manual 6', 1,000 1st stage: Manual 5'6",
	First Extension	N/A
	Second Extension	N/A
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	320 lbs.

Total vertical reach	Fixed
Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	See Above
Below chassis frame reach	N/A
Boom stowed height from mounting surface	4'6"
Crane mounting space requirement	10" x 10"
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Manual 360-degree rotation with handle- brake provides unlimited controlled load positioning
Rotation system brake	Handle Brake, (2) hand-lever controlled rotation stops
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	Includes single hand-crank jack leg stabilizer which requires upfitter supplied and installed Class III receiver
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 20 FT Cord with Quick Disconnect
Control valve type	N/A
Wireless remote included	No

Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	6,000 FT-LBS crane moment rating
Country of origin for crane	USA
Crane Overall Weight	320 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Ventura to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$4,210.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo ESV1000
	Required Frame RBM, SM & PSI of steel	Ford Transit, Knapheide KUV (All models), Reading CSV (All models), Harbor WorkMaster (All models), Royal Service Van, Warner Enclosed Bodies (All models)
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	N/A
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	1st stage: Manual 2-3 ft., 1,000 lbs.
	First Extension	N/A
	Second Extension	N/A
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A

Crane weight	175 lbs.
Total vertical reach	4'9"
Horizontal hook approach from centerline of rotation	N/A
Vertical hook approach from mounting surface	N/A
Total horizontal reach	2-3'
Below chassis frame reach	N/A
Boom stowed height from mounting surface	37-5/8"
Crane mounting space requirement	15" x 13" Floor Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Manual 360-degree rotation with band brake provides unlimited controlled load positioning. Manual 5-pin elevation
Rotation system brake	Band Brake
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	N/A
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 20 FT Cord with Quick Disconnect
Control valve type	N/A
Wireless remote included	No
Number of wireless remote functions	All functions are on remote

Boom Cylinder description	N/A
Crane rating	3,000 FT-LBS crane moment rating
Country of origin for crane	USA
Crane Overall Weight	175 lbs.
Crane Stowed Center of Gravity	N/A
Warranty	Limited policy warrants new products of Venturo to be free from defects in material and workmanship
<b>BASE UNIT PRICE:</b>	<b>\$3,420.00</b>

Price quote for:

## Crane Installed on Cab & Chassis

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Taylor</b>
Street Address:	<b>1130 73rd Avenue NE</b>
P.O. Box:	
City, State, Zip:	<b>Fridley, MN, 55432</b>
Phone #:	<b>763-571-1902</b>
Toll Free #:	<b>1-800-795-1280</b>
Fax #:	<b>763-571-5091</b>
Email Address:	<a href="mailto:jtaylor@crysteeltruck.com">jtaylor@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Vendor Name:	<b>Crysteel Truck Equipment</b>
Contact Person:	<b>Josh Miller</b>
Street Address:	<b>52248 Ember Road</b>
P.O. Box:	
City, State, Zip:	<b>Lake Crystal, MN 56055</b>
Phone #:	<b>507-726-6041</b>
Toll Free #:	<b>1-800-722-0588</b>
Fax #:	<b>507-726-2984</b>
Email Address:	<a href="mailto:jmiller@crysteeltruck.com">jmiller@crysteeltruck.com</a>
Website:	<b>crysteeltruck.com</b>

Spec #	Information Requested	Answer
1.0	<b>MAKE AND MODEL</b>	Venturo VC750FB
	Required Frame RBM, SM & PSI of steel	2016-Current Ford Transit Mid/High Roof
	Lift Capacity at 5' to 9' from centerline of rotation state distance & lift capacity	N/A
	Each extension type, horizontal reach from centerline of rotation and maximum capacity at that length	
	Main Boom	1st stage: Manual 2.6', 750 lbs.
	First Extension	N/A
	Second Extension	N/A
	Third Extension	N/A
	Fourth Extension	N/A
	Fifth Extension	N/A
	Sixth Extension	N/A
	Seventh Extension	N/A
	Crane weight	165 lbs.
	Total vertical reach	5'
	Horizontal hook approach from centerline of rotation	N/A

Vertical hook approach from mounting surface	N/A
Total horizontal reach	2'6"
Below chassis frame reach	N/A
Boom stowed height from mounting surface	63-3/8"
Crane mounting space requirement	12" x 12" Floor Plate
Distance from back of cab to crane clearance	N/A
Distance from crane to front of body clearance	N/A
Crane rotation & rotation working area	Manual 360-degree rotation with band brake provides unlimited controlled load positioning
Rotation system brake	Band Brake
Rotation system Drive	N/A
Rotational torque in ft-lb's	N/A
Outrigger description, width & design	N/A
Outrigger hydraulic description (independent down, stroke length, etc.)	N/A
Outrigger pad size & type	N/A
Throttle control, if any	N/A
Hydraulic pump type, GPM, PSI	N/A
Hydraulic oil reservoir size/description	N/A
Is Hydraulic reservoir heated	N/A
Hydraulic fluid type	N/A
Control locations & Description	Remote Control Pendant: 20 FT Cord with Quick Disconnect
Control valve type	N/A
Wireless remote included	No
Number of wireless remote functions	All functions are on remote
Boom Cylinder description	N/A
Crane rating	1,875 FT-LBS crane moment rating
Country of origin for crane	USA

Crane Overall Weight 165 lbs.

Crane Stowed Center of Gravity N/A

Warranty Limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation.

**BASE UNIT PRICE:** \$3,210.00

# Crane Installed on Cab & Chassis

Venco Ventura

VENDOR: \_\_\_\_\_

MAKE/MOD \_\_\_\_\_  
EL \_\_\_\_\_

## OPTIONS

Spec #	Description	Qty	Price	Subtotal
	<b>BASE UNIT PRICE:</b>		See Previous Sheets	
1.0	-----			
2.0	<b>CRANE EXTENSION OPTIONS</b>			
3.0	<b>OUTRIGGER OPTIONS</b>			
	<b><u>Hydraulic Cranes</u></b>			
3.1	Outrigger: Manual pullouts, manual crank down P/N 24962-CD for HT25KX-P and HT30KX-P		\$1,960.00	\$ -
3.2	Outrigger: Manual pullouts, hydraulic down P/N 24962-PH for HT25KX-P and HT30KX-P		\$4,290.00	\$ -
3.3	Outrigger: Manual pullout, manual crank down P/N 25100-CD for HT45KX's and HT55KX's		\$2,230.00	\$ -
3.4	Outrigger: Manual pullout, hydraulic down P/N 25100-PH-SL (utility body) for HT45KX's and HT55KX's		\$4,410.00	\$ -
3.5	Outrigger: Manual pullout, hydraulic down P/N 25100-PH-LL (platform body) for HT45KX's and HT55KX's		\$4,650.00	
3.6	Outrigger: Hydraulic out, hydraulic down P/N 25100-PHX-SL (utility body)		\$5,320.00	\$ -
3.7	Outrigger: Hydraulic out, hydraulic down P/N 25100-PHX-LL (platform body)		\$5,420.00	\$ -
3.8	Outrigger: Hydraulic out, hydraulic down P/N 27634-PHX-SL (utility body) for HT66KX for Ventura Crane Body		\$7,170.00	\$ -
3.9	Outrigger: Hydraulic out, hydraulic down P/N 27634-PHX-LL (platform body) for HT66KX for Ventura Crane Body		\$7,580.00	\$ -
3.10	Outrigger: Hydraulic out, hydraulic down P/N 27695-PHX-SL for HT66KX for Non-Venturo Body		\$5,900.00	\$ -
3.11	Outrigger: Hydraulic out, hydraulic down P/N 27695-PHX-LL for HT66KX for Non-Venturo Body		\$6,060.00	\$ -
	<b><u>Electric Cranes</u></b>			
3.12	Outrigger: Manual pullout, manual crank down P/N 18500-CD for DT7K, ET8KX, and ET12KX		\$1,270.00	\$ -
3.13	Outrigger: Manual pullout, manual crank down P/N 24962-CD for ET16KX, ET18KX, ET25KXX, and ET30KXX		\$1,960.00	\$ -
3.14	Outrigger: Manual pullouts, hydraulic down P/N 24962-PHE for ET16KX, ET18KX, ET25KXX, and ET30KXX		\$5,050.00	\$ -
3.15	Outrigger: Manual pullouts, manual crank down P/N 25100-CD for ET36KX		\$2,230.00	\$ -
3.16	Outrigger: Manual pullouts, hydraulic down P/N 25100-PHE-SL for ET36KX		\$5,020.00	\$ -
3.17	Outrigger: Manual pullouts, hydraulic down P/N 25100-PHE-LL for ET36KX		\$5,280.00	\$ -
	<b><u>Electric Mast Cranes</u></b>			
3.18	Jackleg drop down stabilizer for utility body P/N 13500		\$360.00	\$ -
3.19	Jackleg drop down stabilizer for platform body P/N 11822-2		\$430.00	\$ -
3.20	Outrigger: Manual pullout/manual crank down P/N 18500-CD		\$1,270.00	\$ -
4.0	<b>REMOTE CONTROLS</b>			
	<b><u>Electric Cranes</u></b>			
4.1	Hand-held push-bottom transmitter and compartment mounted receiver w/ troubleshooting error code display. ILO Standard Corded Remote		\$1,040.00	

4.2	Hand-held push-bottom transmitter and compartment mounted receiver w/ troubleshooting error code display. In Addition to Standard Corded Remote	\$1,440.00	
	<b><u>Electric Mast Cranes</u></b>		
4.3	Hand-held push-bottom transmitter and compartment mounted receiver w/ troubleshooting error code display. ILO Standard Corded Remote	\$1,040.00	
4.4	Hand-held push-bottom transmitter and compartment mounted receiver w/ troubleshooting error code display. In Addition to Standard Corded Remote	\$1,440.00	
5.0	<b>ATTACHMENTS</b>		
6.0	<b>OTHER OPTIONS</b>		
	<b><u>Hydraulic Cranes</u></b>		
6.1	Engine Start/Stop & Throttle Control (Available only with Proportional Controls	\$250.00	\$ -
6.2	Boom Tip Worklight-Connected to anti-two block	\$360.00	\$ -
6.3	E-Z Stow Handle-Stows the load block/hook during transportation	\$170.00	\$ -
6.4	Pumps: 4.0 @ 1,000 RPM, A Flange, 5/8"-9 Spline P/N 19296-4.00 for HT25KX-P and HT30KX-P	\$1,180.00	\$ -
6.5	Pumps: 12 @ 1,200 RPM, B Flange, 7/8"-13 Spline P/N 19296-10.0 for HT45KX-P, HT55KX-P, and HT66KX-P	\$1,490.00	\$ -
6.6	Reservoir: 25 gallon bulkhead mount P/N 22785 for HT45KX-P and HT55KX-P	\$1,210.00	\$ -
6.7	Reservoir: 40 gallon bulkhead mount P/N 22998 for HT66KX-P	\$1,290.00	\$ -
6.8	Mounting Pedestal: 36" high-for platform body P/N 17576-36 for HT25KX-P and HT30KX-P	\$1,070.00	\$ -
6.9	Mounting Pedestal: 36" high- for platform body P/N 17830-36 for HT45KX-P and HT55KX-P	\$1,220.00	\$ -
6.10	Mounting Pedestal: 36" high-for platform body P/N 27656-36 for HT66KX-P	\$1,560.00	\$ -
6.11	Boom Rest: Adjustable 18"-26"-for utility body P/N 20381-2 for HT25KX-P and HT30KX-P	\$460.00	\$ -
6.12	Boom Rest: Adjustable 18"-26"-for utility body P/N 20381-1 for HT45KX-P, HT55KX-P, and HT66KX-P	\$460.00	\$ -
	<b><u>Electric Cranes</u></b>		
6.13	Mounting Pedestal: 21" high for platform body P/N 14930-21 for DT7K	\$740.00	\$ -
6.14	Mounting Pedestal: 36" high for platform body P/N 14930-36 for DT7K	\$880.00	\$ -
6.15	Mounting Pedestal: 21" high for platform body P/N 20480-21 for ET6K	\$630.00	\$ -
6.16	Mounting Pedestal: 36" high for platform body P/N 20480-36 for ET6K	\$670.00	\$ -
6.17	Mounting Pedestal: 21" high for platform body P/N 21571-21 for ET8K and ET12K	\$760.00	\$ -
6.18	Mounting Pedestal: 36" high for platform body P/N 21571-36 for ET8K and ET12K	\$820.00	\$ -
6.19	Mounting Pedestal: 36" high for platform body P/N 21699-36 for ET16KX and ET18KX	\$980.00	\$ -
6.20	Mounting Pedestal: 36" high for platform body P/N 17576-36 for ET25KX, ET30KX, and ET36KX	\$1,070.00	\$ -
6.21	Circuit Breaker Kit: Requires a minimum 250 AMP breaker P/N 22946-250 for DT7K, ET6K, ET8KX, ET12KX, ET16KX, ET18KX,	\$120.00	\$ -
6.22	Circuit Breaker Kit: Requires a minimum 300 AMP breaker P/N 22946-300 for ET25KX, ET30KX, ET36KX	\$130.00	\$ -
6.23	Capacity Overload Alarm: P/N 17356 for ET6K, ET8K, and ET12KX	\$200.00	\$ -
6.24	Boom Rest: Adjustable (13"-19") w/ hook restraint P/N 21440 for ET6K, ET8K, ET12KX	\$430.00	\$ -
6.25	Boom Rest: Adjustable (18"-26") for utility body P/N 20381-2 for ET16KX, ET18KX, ET25KX, ET30KX, and ET36KX	\$460.00	\$ -
	<b><u>Electric Mast Cranes</u></b>		
6.26	Circuit Breaker Kit: Requires a minimum 150 AMP breaker P/N 22946-150 for CE1500FB, CE6K	\$100.00	\$ -

6.27	Circuit Breaker Kit: Requires a minimum 250 AMP breaker P/N 22946-250 for CE6K, CT2003FB, and CT310KX	\$120.00	\$ -
6.28	Extra Sockets: Type "A" Flush Mount P/N 13171 for CT2003FB	\$250.00	\$ -
6.29	Extra Sockets: Type "C" Surface Mount P/N 13172 for CT2003FB	\$280.00	\$ -
6.30	Short Mast: (Specify Height) CT Series Only	\$210.00	\$ -
6.31	Quick Disconnect Socket & Plug P/N 11645 for CT2003FB	\$140.00	\$ -
	<b>Van Cranes</b>		
6.32	Circuit Breaker Kit: Requires a minimum 150 AMP breaker P/N 22946-150 for all van cranes	\$100.00	\$ -
7.0	<b>CUSTOM WORK</b>		
7.1	White/Black Paint P/N 24838	\$400.00	\$ -
7.2	Red/Yellow/Blue/Green or similar P/N 24838-1	\$610.00	\$ -
7.3	White/Black Paint P/N 24838-2	\$370.00	\$ -
7.4	Red/Yellow/Blue/Green or similar P/N 24838-3	\$570.00	\$ -
8.0	<b>DISCOUNT OFF LIST PRICE FOR RELATED PARTS AND ACCESSORIES</b>		
	<b>% Discount</b>	0.00%	
	<b>Price List Date and Number</b>	N/A	
9.0	<b>DELIVERY CHARGES</b>		
	<b>DELIVERY STARTING POINT - City, State, Zip</b> Lake Crystal, MN 56055 or Fridley, MN 55432		
	Price per loaded mile	\$ 1.95	\$ -
10.0	<b>Per Hour SHOP RATE</b>		
10.1	<b>EQUIPMENT INSPECTION AND REPAIR</b>	\$ 95.00	\$ -
10.2	<b>INITIAL INSPECTION/DIAGNOSTIC</b>	\$ 95.00	\$ -
10.3	<b>MECHANICAL REPAIRS</b>	\$ 95.00	\$ -
	<b>Total Cost:</b>	\$	\$ -