

2010 Bituminous Spec Change Highlights

01/19/2010

1. English Units are now presented first and metric second in brackets [].
2. Any reference to Marshall mix design has been removed.
3. All reference to VMA has been removed.
4. 2360.2 A2h (page 3) New section on shingles.
5. Table 2360.2E (page 6) Includes a -3/8" gradation.
6. 2360.2F (page 6) Additives, Approval of additives now with Engineer rather than Bit. Engineer.
7. 2360.2G1 (page 8) Asphalt Binder/RAP selection Table change.
8. 2360.3A Mix Design AASHTO T-312 is now (MnDOT Modified) so it excludes internal angle requirement.
9. 2360.3 B1 (page 9) Included submittal size of RAS when it is used in mix.
10. Table 2360.3-B2a (page 10) Table now includes Shingle allowances. Table also includes AFT.
11. 2360.3 B2c (page 11) previous VMA table now called primary control table to define coarse and fine mixes.
12. 2360.3 B2d (page 11) Included AFT requirement.
13. 2360.4 D (page 17) Changed sample retention from 7 working days to 10 calendar days.
14. Table 2360.4-E (page 18) Changed gradation test rate.
15. Table 2360.4-D & E (page 18) include AFT.
16. Table 2360.4 H (page 24) JMF table includes AFT
17. 2360.4 J1 (page 24) Removed wording relating to JMF change on #200.
18. 2360.4 L (page 25) Section includes AFT.
19. Table 2360.4- L6 and Section 2360.4 L7 (page 28) Changed pay factor for gradation from 80% to 90% and reworded
20. 2360.5 C2d (page 33) Added Distributor
21. 2360.6 Density (page 35) complete change of density section to include long joint requirement.
22. 2360.6 B2a (page 38) Included clarification on where to cut edge cores.