

WORK PLAN [Draft 03/07/2017]
2017 MnROAD Unbound Layer Evaluation Using Intelligent Compaction
Ingios Geotechnics, Inc.

Problem Statement

Re-construction of the 2017 MnROAD-NRRA low volume and mainline road test sections will involve several pavement and foundation materials (recycled materials and large aggregate bases) that will be evaluated and tested during construction and long-term (see Appendix).

Although the final evaluation details are currently being developed, key research objectives include:

- Developing and accessing methods to characterize the pavement foundation materials as part of the quality inspection process,
- Assessing pavement system performance properties over time (drainability, modulus of foundation layers, deformation under traffic loading, durability, and uniformity), and
- Determining best practices for how to incorporate the measured in situ properties and pavement system performance results into pavement design for future implementation.

Ingios Geotechnics, Inc. has expertise in pavement system characterization and assessment of pavement design input values using automated plate load testing (APLT), validated integrated compaction monitoring (VICM), and geospatial drainage assessment using in situ pavement permeameter test (PPT) measurements. Ingios has prepared the following work plan details are part of the proposed no-cost partnership agreement with MnDOT to provide testing and analysis for selected test sections.

Project Goals

The goal of this Ingios testing and analysis is to develop spatial coverage maps of calibrated mechanistic design input parameter values (e.g., resilient/elastic modulus, modulus of subgrade reaction) on finished unbound foundation layers for the test cells identified in Table 1.

Scope of Work

To achieve the project goal, the following scope of work and associated project tasks have been identified:

1. Mobilize Ingios vibratory compactor outfitted with the VICM and RTK-GPS system along with the APLT and PPT to MnROAD.
2. Conduct on-site safety briefing with all personnel involved with Ingios activities prior to initiating work tasks.
3. Using the VICM equipped roller (Figure 1), map the cell areas listed in Table 1 to produce various index and modulus map results.
4. Perform independent field calibration testing, involving 12 to 20 test locations using the APLT (Figure 2). This process will include testing areas of interest in the designated cells based on the VICM mapping results. APLTs will involve using a 12, 18, 24, or 30 in. diameter plate with a 2-layer sensor kit to obtain stress-dependent moduli values for

both the aggregate base and the underlying subgrade layer. The plate diameter and testing approach will be determined based on the VICM results.

5. Perform five PPTs (Figure 3) in each cell. Select an additional one to three cells to perform a spatial test point layout (20 to 40 test points) for drainage analysis.
6. Select up to three test locations for extended cycle APLT permanent deformation tests to characterize the permanent deformation response of the foundation layer system under cyclic loading with up to 10,000 loading cycles.
7. Produce data summary and calibration reports.
8. Provide raw data in formats requested by MnDOT.
9. Pending input from state DOT design engineers, provide recommendations for implementation of test results in term of each state design methodology.
10. Prepare a brief webinar to summarize all findings and deliver to NRRRA groups as requested.

A review of the current pavement design procedures for the participating NRRRA states was conducted and summarized in Table 2. The design input parameters are elastic modulus (E), resilient modulus (M_r), modulus of subgrade reaction (k), R-value, California bearing ratio (CBR), and structural layer coefficients which are correlated to resilient modulus. In the field calibration efforts with VICM, field testing will be conducted using stress-dependent M_r or E and k-value determined from APLT testing.

Successful completion of the proposed testing is contingent upon being provided timely updates as to construction schedules and access timeline for the cells/completed unbound layers. The partnership agreement outlines Ingios and MnDOT responsibilities to facilitate successful and safe completion of the proposed testing.

Table 1. Proposed MnROAD test cells and unbound layers for evaluation by Ingios research team

Roadway	2017 Study	Cell	Unbound Distances (Feet)	Unbound Materials to Compact (layers - bottom to top)
Low Volume Road	PCC Early Traffic Opening	124 - 424	507	Top of sand Subgrade 6" Class 6 Aggregate Base
	Large Subbase Aggregate [3.5 in. HMA Standard Mix]	127	282.5	Top of clay subgrade 18" large aggregate subbase (1 lift) 6" Class 6 Aggregate Base
		227	285	Top of clay subgrade 18" large aggregate subbase (2 lifts) 6" Class 6 Aggregate Base
		128	285	Top of clay subgrade 9" large aggregate subbase 6" Class 6 Aggregate Base
		228	285	Top of clay subgrade 9" large aggregate subbase 6" Class 5Q Aggregate Base
	Fiber Reinforced PCC	139	280	Top of clay Subgrade 4" common borrow 6" Class 5 Aggregate Base
		239	285	
Mainline	Fiber Reinforced PCC	506	134	Top of 3" existing Class 5 11" Class 5Q Aggregate Base
		606	135	
		706	135	
		806	135	

Table 2. Summary of pavement foundation layer inputs with existing pavement design procedures at the NRRRA participating states.

STATE	PAVEMENT	DESIGN DESCRIPTION	SUBGRADE INPUTS	BASE/SUBBASE INPUTS
CA	Flexible	HMA and base/subbase layer thickness based on R-value of the subgrade and Traffic Index	R-Value ¹	R-Value ¹
	Rigid	PCC and base/subbase layer thickness based on R-value of the subgrade and Traffic Index	R-Value ¹	Resilient Modulus ²
IL	Flexible	Modified AASHTO Design procedure. Thickness design based on traffic factor and estimated structural number.	IBR value	Structural layer coefficients (a ₂ , a ₃)
	Rigid	Modified AASHTO Design procedure. Thickness design based on traffic factor and IBR or k-value.	IBR value or k-value ³	N/A [only minimum thickness]
MI	Flexible	Pavement ME Design [Similar to AASHTOWare™] – Level 2 or 3 (Typical values)	Resilient Modulus ²	Resilient Modulus ²
	Rigid	Pavement ME Design [Similar to AASHTOWare™] – Level 2 or 3 (Typical values)	Resilient Modulus ²	Resilient Modulus ²
MO	Flexible	AASHTO Pavement ME Design	Resilient Modulus ⁶	Resilient Modulus ⁶
	Rigid	AASHTO Pavement ME Design	Resilient Modulus ⁶	Resilient Modulus ⁶

STATE	PAVEMENT	DESIGN DESCRIPTION	SUBGRADE INPUTS	BASE/SUBBASE INPUTS
MN	Flexible	MnPAVE-Flexible with basic, intermediate, and advanced level. Advanced level requires moduli of all layers, while basic and intermediate levels require typical values or DCP test results, R-value results.	R-value ⁴ (basic/int) or Resilient Modulus (advanced)	DCP index ⁴ (basic/int) or Resilient Modulus (advanced)
	Rigid ⁵	MnPAVE-rigid uses MEPDG level 3 based design procedure.	Resilient modulus	Resilient Modulus
WI	Flexible	AASHTO 1972 design procedure. Thickness design based on design ESALs, soil support value, and estimated structural number.	Soil support value (correlated to CBR)	Structural layer coefficients (a ₂ , a ₃)
	Rigid	AASHTO 1972 design procedure. Thickness design based on design ESALs, working stress, and modulus of subgrade reaction (k)	k-value	NA

¹California R-value is a measure of resistance to deformation of the soils under saturated conditions and traffic loading as determined by the stabilometer test (CT301). Typical range between 5 (very soft) to 80 (treated base material). Typical values provided based on soil classification/ region.

²Typical resilient moduli values are provided in the design guide based on the material type.

³Illinois bearing ratio (IBR) is a slight modification of CBR test run after 4-days of soaking. Typical values are provided based on soil classification (ranges between 2 and 20). Modulus of subgrade reaction (k) value vs. IBR is provided in the design nomographs.

⁴Minnesota R-value determined from modulus value ($R = [0.41 + 0.873 * (\text{subgrade modulus} / 1000)]^{1.28}$)

⁵MnPAVE-Rigid design procedure for PCC bonded overlay over HMA uses the ACPA procedure to determine composite k-value based on subgrade k-value and aggregate layer resilient modulus. <http://apps.acpa.org/applibray/KValue/>

⁶personal communication, 03/02/2017, John P. Donahue, P.E., Construction and Materials Liaison Engineer, MoDOT

CalTrans Highway Design Manual - http://www.dot.ca.gov/hq/oppd/hdm/pdf/english/HDM_Complete_07Mar2014.pdf

ILDOT Pavement Design Manual - <http://www.idot.illinois.gov/Assets/uploads/files/Doing-Business/Manuals-Split/Design-And-Environment/BDE-Manual/Chapter%2054%20Pavement%20Design.pdf>

MDOT User Guide for ME Pavement Design:

https://www.michigan.gov/documents/mdot/MDOT_Mechanistic_Empirical_Pavement_Design_User_Guide_483676_7.pdf

MnDOT Pavement Design Manual: www.dot.state.mn.us/materials/pvmtdesign/manual.html

WIDOT Facilities Development Manual: <http://wisconsin.dot.gov/rdwy/fdm/fd-14-10.pdf>






Figure 1. Ingios VICM equipped roller, calibration verification plot, and example output.



Model: AASHTO (2015)

$$M_r = k_1^* P_a \left(\frac{\theta}{P_a} \right)^{k_2^*} \left(1 + \frac{\tau_{oct}}{P_a} \right)^{k_3^*}$$

Parameter	Value	P-Value
$k_1^* (Base)$	3129.4	1.00E-06
$k_2^* (Base)$	0.400	2.97E-02
$k_3^* (Base)$	-1.875	8.86E-02
Adj. R^2	0.863	
Std. Error [psi]	2280	
$k_1^* (Subgrade)$	494.7	8.29E-05
$k_2^* (Subgrade)$	-0.296	1.45E-01
$k_3^* (Subgrade)$	0.812	6.95E-01
Adj. R^2	0.937	
Std. Error [psi]	326	

Figure 2. Ingios APLT system with 2-layered sensor measurement kit for measurement of stress-dependent resilient modulus and AASHTO (2015) universal model parameters.





Figure 3. Ingios PPT equipment and geospatial drainage time analysis output.

2017 MnROAD-NRRA CONSTRUCTION

Low Volume Road



Cold Central Plant Recycling (CCPR)							Reduced Cementitious PCC			PCC Early Traffic Opening	
Original	Original	Original	New	New	New	New	Original	New	New	Original	New
33	34	35	133	233	135	235	38	138	238	24	124 - 424
4" 58-34 PPA	4" 58-34 SBS+PPA	4" 58-34 SBS	4" CCPR (Emulsion)	4" CCPR (Foam)	4" CCPR (Foam)	4" CCPR (Emulsion)	6" Trans Tined 15'Lx12'W 1" dowel	8" PCC w/ Optimized Mix Design A 15'Lx12'W 1" dowel	8" PCC w/ Optimized Mix Design B 15'Lx12'W 1" dowel	3" 58-34	6" PCC 15'Lx12'W 1" dowel
12" Class 6	12" Class 6	12" Class 6	12" Class 6	12" Class 6	12" Class 6	12" Class 6	5" Class 5	5" Class 5	5" Class 5	4" Class 6	6" Class 6
Clay	Clay	Clay	Clay 1" Double Chip Seal	Clay 1" Double Chip Seal	Clay 1.5" HMA Overlay	Clay 1.5" HMA Overlay	Clay	Clay	Clay	Sand 100' Fog Seals 2008-2012	Sand
Sep 07	Sep 07	Sep 07	2017	2017	2017	2017	Jul 93	2017	2017	Oct 08	2017
500	499	499	425	425	425	437	480	257.5	260	507	507
71			132				67			41	

Fiber Reinforced PCC			Recycled Unbound Base							
Original	New	New	Original	Original	Original	Original	New	New	New	New
39	139	239	85	86	88	89	185	186	188	189
4" Perv Overlay	3" Fiber Reinf PCC	4" Fiber Reinf PCC	7" Pervious PCC	5" Porous HMA	5" Porous HMA	7" Pervious PCC	3.5" HMA	3.5" HMA	3.5" HMA	3.5" HMA
6" 20'Lx12'W 1" dowel	6" Class 5	6" Class 5	4" RR Ballast	4" RR Ballast	4" RR Ballast	4" RR Ballast	12" Coarse RCA	12" Fine RCA	12" Limestone Aggregate Class 6	12" Recycled Aggregate Base Class 6
5" Class 5	4" Common Borrow	4" Common Borrow	8" CA-15	10" CA-15	10" CA-15	8" CA-15	3.5" Select Granular Borrow	3.5" Select Granular Borrow	3.5" Select Granular Borrow	3.5" Select Granular Borrow
Clay	Clay	Clay	Type V Geo-Textile	Type V Geo-Textile	Type V Geo-Textile	Type V Geo-Textile	Sand	Sand	Clay	Clay
Oct 08	2017	2017	Oct 08	Oct 08	Oct 08	Oct 08	2017	2017	2017	2017
440	280	285	216	235	225	217	216	235	225	217
67			43							

Large Subbase Aggregate			Large Subbase Aggregate			Compacted Concrete Pavement (CCP)			PCC Diamond Grinding ASR	
Original	New	New	Original	New	New	Original	New	New	Original	New
27	127	227	28	128	228	32	132	232	32	141-143, 241-243, 341-343, 441-443
2" 52-34	3.5" HMA	3.5" HMA	6" SFDR Chip Seal	3.5" HMA	3.5" HMA	5" Astro Turf 10Lx12W	5" CCP w/ Fibers	5" CCP	5" CCP	Refer to the note below
2" 58-34	6" Class 6	6" Class 6	2012 Spot Repairs Fog Seal	6" Class 6	6" Class 5Q	Class 1f	7" Class 5Q	7" Class 5Q	7" Class 5Q	
6" Class 5	18" Large Aggregate Subbase 1 lift	18" Large Aggregate Subbase 2 lifts	4" Class 5	9" Large Aggregate Subbase	9" Large Aggregate Subbase	6" Class 1c	20'Lx12'W Unsealed Joints	20'Lx12'W Unsealed Joints	12'Lx12'W Unsealed Joints	
G CBD	Clay	Clay	2009 Chip Seal	Clay	Clay	Clay	Clay	Clay	Clay	
2009 Chip Seal			7" Clay Borrow							
7" Clay Borrow			Clay							
Clay										
Aug 06	2017	2017	Sep 11	2017	2017	Jun 00	2017	2017	2017	Jul 93
499	282.5	285	500	285	285	460	150	150	170	
68			65			0				

Note: Plan view for Cells 141 - 443

Cell	141	241	341	441	142	242	342	442	143	243	343	443
Outside Lane	No Work	Sealer	Diamond grind (0.25" removal) Sealer	Diamond grind (0.25" removal)	Diamond grind (0.25" removal)	Diamond grind (0.25" removal) Sealer	Sealer	No Work	Diamond grind (0.25" removal)	Diamond grind (0.25" removal) Sealer	Sealer	No Work
Inside Lane	No Work	Sealer	Diamond grind (0.25" removal) Sealer	Diamond grind (0.25" removal)	Diamond grind (0.25" removal)	Diamond grind (0.25" removal) Sealer	Sealer	No Work	Diamond grind (0.25" removal)	Diamond grind (0.25" removal) Sealer	Sealer	No Work