

TYPE C PORTABLE CHANGEABLE MESSAGE SIGNS

Manufacturer	American Signal
Model	T333
Contact Person	Tim Paulino
Phone Number	770-448-6650 ext 12. Cell: 404-353-6388
Full Matrix, Continuous Line Matrix, or Character Matrix?	Full Matrix
Character Height and Width (Max)	18.25" x 13"
Pixel Aspect Ratio of "H" (H x W)	7 x 5
Pixel Dimensions (H x W)	1.5" x 2"
Minimum Character to Character Space	3.25". Varied spacing according to number and type of characters on a line.
Space Between Lines	9.75"
LEDs per Pixels	4
LED Description	Amber 590nm AllnGaP 17° wide
Panel Dimensions	137.5" x 79"
Type of Programming Device	Handheld with LCD readout
Lighted Programming Console?	Lit LCD readout.
Ease of Programming	Difficult. Too many steps to do a quick message. Must create message and then sequence.
Ease of Setup Including Sighting	Different. Requires the use of a wrench to lock and unlock the rotation feature. Must fully raise display before locking rotation. Requires climbing on unit.
Angularity Distance (ft)	100'

Trailer Information

Tire Size	205/75 D15
Radial?	No
Welded Construction?	Yes
Advertised Windload	104 mph wind gusts.
Battery Description	12 volt system. 12 - 6 volt Deka Promaster.
Solar Array Wattage	369 Watt. 3 - 123W Sharp
Steppable Fenders?	Yes
Weight	3000 lb.

Comments: Surge brakes. Have to make sure there is a wrench of the proper size before venturing out to deploy device.