

TYPE C PORTABLE CHANGEABLE MESSAGE SIGNS

Manufacturer	Ver-Mac
Model	1210
Contact Person	Eric Johnson
Phone Number	612-521-2122
Full Matrix, Continuous Line Matrix, or Character Matrix?	Character Matrix
Character Height and Width (Max)	18" x 13"
Pixel Aspect Ratio of "H" (H x W)	7 x 5
Pixel Dimensions (H x W)	2" x 2"
Minimum Character to Character Space	2.5"
Space Between Lines	3.5"
LEDs per Pixels	4
LED Description	Amber. 17° view angle
Panel Dimensions	133" x 71"
Type of Programming Device	Standard keyboard with LCD readout. Handheld optional.
Lighted Programming Console?	LCD readout is lit.
Ease of Programming	Somewhat difficult to get rid of additional phases in a sequenced message.
Ease of Setup Including Sighting	Good. Used a compression ring to lock rotation. May be aimed from ground.
Angularity Distance (ft)	150'

Trailer Information

Tire Size	F78-15
Radial?	Yes
Welded Construction?	Yes
Advertised Windload	
Battery Description	12 volt system. 12 - 6 volt Pow-R-Surge.
Solar Array Wattage	165 Watt. 3 - 55W. Mitsubishi
Steppable Fenders?	Yes
Weight	3600 lb.

Comments: Surge brakes. Electric brakes are an option. Old style trailer. No hold down latch for battery box lids. Bungee cord attached to display cable. Cable can drag.