

TYPE C PORTABLE CHANGEABLE MESSAGE SIGNS

Manufacturer	Ver-Mac
Model	1500
Contact Person	Eric Johnson
Phone Number	612-521-2122
Full Matrix, Continuous Line Matrix, or Character Matrix?	Full Matrix
Character Height and Width (Max)	17.5" x 12"
Pixel Aspect Ratio of "H" (H x W)	7 x 5
Pixel Dimensions (H x W)	2" x 2"
Minimum Character to Character Space	3". Varied spacing according to number and type of characters on a line.
Space Between Lines	8" (4 pixels)
LEDs per Pixels	4
LED Description	Amber. 22° view angle?
Panel Dimensions	133" x 83"
Type of Programming Device	Standard keyboard with LCD readout. Handheld optional.
Lighted Programming Console?	LCD readout is lit.
Ease of Programming	Somewhat difficult to get rid of additional phases in a sequenced message.
Ease of Setup Including Sighting	Good. Uses a compression ring to lock rotation. May be aimed from ground.
Angularity Distance (ft)	100'

Trailer Information

Tire Size	205/75-15
Radial?	Yes
Welded Construction?	Yes
Advertised Windload	
Battery Description	12 volt system. 12 - 6 volt Interstate U2200.
Solar Array Wattage	220 Watt. 2 - 110W Mitsubishi
Steppable Fenders?	Yes
Weight	3800 lb.

Comments: Surge brakes. Electric brakes are an option. Plastic boxes for batteries. Trailer was well balanced. Tongue could be lifted by hand.