

TYPE C PORTABLE CHANGEABLE MESSAGE SIGNS

Manufacturer	Wanco
Model	WTLMB-SLL
Contact Person	Don Tauchen
Phone Number	630-207-5247
Full Matrix, Continuous Line Matrix, or Character Matrix?	Character Matrix
Character Height and Width (Max)	18" x 13"
Pixel Aspect Ratio of "H" (H x W)	7 x 5
Pixel Dimensions (H x W)	2" x 2"
Minimum Character to Character Space	2.5"
Space Between Lines	5"
LEDs per Pixels	4
LED Description	Amber. 24° view angle
Panel Dimensions	130" x 72"
Type of Programming Device	Standard keyboard with LCD readout.
Lighted Programming Console?	Yes
Ease of Programming	Very easy. All instructions for a quick sign are printed alongside the readout.
Ease of Setup Including Sighting	Good. Nice disk brake rotation lock. Can be sighted from ground.
Angularity Distance (ft)	75'

Trailer Information

Tire Size	205/75-15
Radial?	No
Welded Construction?	Yes
Advertised Windload	98 mph with outriggers
Battery Description	12 volt system. 8 - 6 volt Exide GC 135.
Solar Array Wattage	240 Watt. 2 - 120W. Kyocera
Steppable Fenders?	No
Weight	2640lb.

Comments: No brakes needed with light weight. Outriggers offered as an option. Needed because of light weight? Cable to display good. Only unit to have tongue wheel with screw jack. Raised edge around each character module prevents light bleeding into next character. Trailer is well balanced.